



LED product catalogue



2021

About GLP

The Global Leader Power brand was created in 2012 as a direct response to LED and Automation market customer needs. It is based on the foundations and experience of Middle Europe's biggest LED driver supplier. Our products are now available all over the European continent.

Our goal is to deliver products that fulfill the restrict requirements of LED market, which is our priority. Compared to other products available on the market today, all Global Leader Power are characterized by innovative PCB Design, high quality components, well established standard dimensions and a very competitive price to quality ratio.

Most of our products are offered with a 5 year warranty, which is exceptional on the global market among professional LED drivers. We wish our customers to take part in the most demanding projects possible all over Europe.

Our motto is: clear cooperation and distribution principles supported by responsible Brand recognition management. One of fundamental goals of Global Leader Power is to become a strong European brand that is independent from large international syndicates. The main goal is to be able to compete with Eastern brands whose policy is sometimes inconsistent and quality is arguable.

Experienced European market of power supplies leaves a large field for improvement so that we offer you Global Leader Power brand.

We welcome you to contact with our European representatives.

Our portfolio also includes AGM batteries – should you be interested, please feel free to contact your local distributor.

So far, Global Leader Power has sold millions of GLP brand devices that already work all over the world.

We are looking forward to our cooperation - become a member of GLP Team!

Contents

AGV/AGC p.4

AGV-12
AGV-16
AGC-12
AGC-16
AGC-25

GPV p.5

GPV-12
GPV-18
GPV-20
GPV-35
GPV-50
GPV-60
GPV-75
GPV-100
GPV-120
GPV-150N
GPV-150
GPV-200

GPVP/GTPC p.6

GPVP-25
GPVP-40
GPVP-60N
GPVP-90
GPVP-120
GTPC-8-12
GTPC-15-12
GTPC-30-12
GTPC-50-12

GTPC-S/GPC p.7

GTPC-30-S
GTPC-45-S
GTPC-60-S
GTPC-75-S
GTPC-100-S
GPC-9
GPC-20
GPC-35
GPC-60

GPCP/GLG p.8

GPCP-20
GPCP-35
GPCP-60
GLG-60
GLG-100
GLG-150
GLG-200
GLG-300

GLSV/GPF p.9

GLSV-035B
GLSV-050B
GLSV-075B
GLSV-100B
GLSV-150B
GLSV-200B
GLSV-320B
GPF-25D
GPF-40D
GPF-60D

PCC p.10

PCC09W-DC-TDim-350
PCC09W-DC-TDim-700
PCC12W-DC-TDim-700
PCC18W-DC-TDim-350
PCC40W-MC-MATCH-900
PCC40W-MC--MATCH1400
PCC60W-MC--MATCH1400
PCC40W-DC-DALI

PCL/GWP p.11

PCL35W-MC-MATCH-700
PCL50W-MC-MATCH-1050
PCL80W-MC-MATCH-1550
GWP-600

AGV/AGC 12-25 W (IP40)

● Features:

- Constant voltage (AGV) / current (AGC) design
- Universal AC input / Full range
- Current versions: 350 mA, 500 mA
- Cooling by free air convection
- 100% full load burn-in test
- Isolation class II
- Double insulation of Input and output wires
- Excellent quality / price ratio
- Up to 3 years warranty



IP40 CE LPS

	Photo	DC voltage	Rated current	Rated power	Protections	Safety & EMC regulations	Working temperature	Dimensions (L x W x H)	Weight
AGV-12		12 V	1 A	12 W	short circuit, over current, over voltage, over temperature	EN 55015, EN 61547	-10°C – +70°C	90 x 40 x 23.5 mm	0.88 kg
AGV-16			1.33 A	15.96 W	short circuit, over current, over voltage				0.90 kg
AGC-12		9-39 V	350 mA	12.6 W	short circuit, over temperature				0.88 kg
AGC-16		18-48 V	350 mA	16.8 W				0.90 kg	
AGC-25		25-50 V	500 mA	25 W				110 x 45 x 24 mm	0.170 kg



GPV 12-200 W waterproof (IP67)

● Features:

- Constant voltage design
- Universal AC input / Full range (except GPV-18)
- Cooling by free air convection
- 100% full load burn-in test
- Isolation class II
- Fully encapsulated with IP67 level
- Excellent quality / price ratio
- Up to 5 years warranty



	Photo	DC voltage	Rated current	Rated power	Protections	Safety & EMC regulations	Working temperature	Dimensions (L x W x H)	Weight
GPV-12		12 V	1 A	12 W	short circuit, over current, over voltage	EN 55015, EN 61347-2-13	-30°C – +70°C	129.5 x 25 x 20 mm	0.13 kg
		24 V	0.50 A						
GPV-18		12 V	1.5 A	18 W	short circuit, over current			129.5 x 25 x 21 mm	0.15 kg
		24 V	0.75 A						
GPV-20		5 V	3 A	15 W	short circuit, over current, over voltage, over temperature			140 x 32 x 25 mm	0.20 kg
		12 V	2 A	24 W					
		15 V	1.33 A	20 W					
		24 V	1 A	24 W					
GPV-35		5 V	6 A	30 W	short circuit, over current, over voltage			148 x 32 x 28 mm	0.20 kg
		12 V	3 A	36 W					
		15 V	2.4 A						
		24 V	1.5 A						
		36 V	1 A						
GPV-50		12 V	4.2 A	50.4 W	short circuit, over current, over voltage, over temperature			148 x 40 x 34 mm	0.34 kg
		24 V	2.1 A						
GPV-60		5 V	8 A	50 W	short circuit, over current, over voltage			162 x 42 x 33 mm	0.39 kg
		12 V	5 A	60 W					
		15 V	4 A						
		24 V	2.5 A						
		36 V	1.67 A						
GPV-75		12 V	6 A	72 W	short circuit, over current, over voltage			162 x 42 x 33 mm	0.38 kg
		24 V	3 A						
GPV-100		12 V	8.3 A	99.6 W	short circuit, over current, over voltage, over temperature			187 x 52 x 37 mm	0.62 kg
		24 V	4.2 A	100.8 W					
		36 V	2.8 A						
GPV-120		12 V	10 A	120 W	short circuit, over current, over voltage, over temperature			203 x 70 x 45 mm	1.15 kg
		24 V	5 A	120 W					
GPV-150N		12 V	12.5 A	150 W	short circuit, over current, over voltage, over temperature			203 x 70 x 45 mm	1.15 kg
GPV-150		24 V	6 A	150 W				203 x 70 x 45 mm	1.15 kg
GPV-200		12 V	16 A	192 W				205 x 70 x 45 mm	1.2 kg
		24 V	8.3 A	200 W					

GPVP double isolation cables 25-120 W waterproof (IP67)

● Features:

- Double insulated wires
- Constant voltage design
- Universal AC input / Full range
- Built-in active PFC function, PF > 0.9
- Cooling by free air convection
- 100% full load burn-in test
- Fully encapsulated with IP67 level
- Excellent quality / price ratio
- Up to 5 years warranty

□ ○ IP67 CE SELV

	Photo	DC voltage	Rated current	Rated power	Protections	Safety & EMC regulations	Working temperature	Dimensions (L x W x H)	Weight		
GPVP-25		12 V	2 A	24 W	short circuit, over current, over voltage, over temperature	EN 55015, EN61347-1, EN61347-2-13	-30°C – +70°C	138 x 42.5 x 34 mm	0.360 kg		
		24 V	1 A								
GPVP-40		12 V	3.5 A	36W	short circuit, over current					149 x 32 x 28 mm	0.23 kg
		24 V	1.7 A								
GPVP-60N		12 V	5 A	60 W	short circuit, over current, over voltage					162 x 42 x 33 mm	0.40 kg
		24 V	2.5 A								
GPVP-90		12 V	7.5 A	90 W	short circuit, overload over current, over voltage, over temperature					190 x 63 x 38 mm	0.391 kg
		24 V	3.75 A								
GPVP-120		12 V	10 A	120 W						250 x 70 x 45 mm	1.05 kg
		24 V	5 A								

GTPC 8-50 W (IP20)

● Features:

- Constant voltage design
- Universal AC input range
- Cooling by free air convection
- 100% full load burn-in test
- Terminal block for quick connection
- Isolation class II
- Flat design
- Up to 2 years warranty

□ ○ CE SELV F

	Photo	Voltage range	Rated current	Rated power	Protections	Safety & EMC regulations	Working temperature	Dimensions (L x W x H)	Weight
GTPC-8-12		12 V	0.67 A	8 W	short circuit, over temperature	EN 55015, EN61347-2-13, EN61000-3-2 Class C	-20°C – +50°C	108 x 35 x 21.5 mm	0.04 kg
GTPC-15-12			1.25 A	15 W				113 x 44 x 20 mm	0.08 kg
GTPC-30-12			2.5 A	30 W				182 x 44 x 16 mm	0.12 kg
GTPC-50-12			4.2 A	50 W				60 x 180 x 24 mm	0.26 kg

GTPC-S 30-100 W (IP20)

Features:

- Power supply from European voltage 220-240Vac
- Output design 12V, 24V
- Built-in active PFC function
- Cooling by free air convection

- Standard reference load
- Ultra thin and slim case size
- Up to 3 years warranty

CE      SELV

	Photo	Voltage range	Rated current	Rated power	Protections	Safety & EMC regulations	Working temperature	Dimensions (L x W x H)	Weight	
GTPC-30-S		12 V	2.50 A	30 W	short circuit, over voltage, overload	EN 55015, EN61347-2-13, EN61000-3-2 Class C	-10°C – +70°C	251 x 30 x 16.5 mm	0.130kg	
		24 V	1.25 A							
GTPC-45-S		12 V	3.75 A	45 W				251 x 30 x 16.5 mm	0.130kg	
		24 V	1.90 A							
GTPC-60-S		12 V	5.00 A	60 W			305 x 30 x 17 mm			0.160kg
		24 V	2.50 A							
GTPC-75-S		12 V	6.25 A	75 W				305 x 30 x 17 mm	0.160kg	
		24 V	3.125 A							
GTPC-100-S		12 V	8.34 A	100 W			320 x 30 x 18.2 mm			0.170kg
		24 V	4.17 A							

GPC 9-60 W waterproof (IP67)

Features:

- Constant current design
- Universal AC input / Full range
- Output current versions: 350mA, 700mA, 1050mA, 1400mA, 1750mA
- Cooling by free air convection

- 100% full load burn-in test
- Isolation class II
- Fully encapsulated with IP67 level
- Excellent quality / price ratio
- Up to 3 years warranty

 IP67 CE LPS

	Photo	Voltage range	Rated current	Rated power	Protections	Safety & EMC regulations	Working temperature	Dimensions (L x W x H)	Weight	
GPC-9		3~24 V	350 mA	8.4 W	short circuit, over temperature	EN 55015, EN 61347-2-13	-30°C – +70°C	129.5 x 25 x 20 mm	0.13 kg	
		2~12 V	700 mA							
GPC-20		9~48 V	350 mA	16.8 W	short circuit				140 x 32 x 25 mm	0.20 kg
		3~28 V	700 mA	19.6 W						
GPC-35		30~80 V	350 mA	28 W					149 x 32 x 28 mm	0.25 kg
		9~48 V	700 mA	33.6 W						
		9~30 V	1050 mA	31.5 W						
		9~24 V	1400 mA	33.6 W						
GPC-60		12~60 V	1050 mA	63 W					162 x 42 x 33 mm	0.36 kg
		9~42 V	1400 mA	58.8 W						
		9~36 V	1750 mA	63 W						

GPCP 20-60 W waterproof (IP67)

● Features:

- Constant current design
- Universal AC input / Full range
- Built-in active PFC function
- Cooling by free air convection
- Current versions: 350 mA, 700 mA, 1050 mA, 1250 mA, 1400 mA, 1750 mA, 2100 mA
- 100% full load burn-in test
- Isolation class II
- Excellent quality / price ratio
- Up to 5 years warranty

☐ IP67 CE LPS

	Photo	Voltage range	Rated current	Rated power	Protections	Safety & EMC regulations	Working temperature	Dimensions (L x W x H)	Weight
GPCP-20		12~48 V	350 mA	16.8 W	short circuit, over current, over voltage, over temperature	EN 55015, EN61347-1, EN61347-2-13	-20°C – +70°C	140 x 32 x 25 mm	0.21 kg
		9~30 V	700 mA	21 W					
GPCP-35		40~80 V	350 mA	28 W	short circuit, over current		-30°C – +70°C	149 x 32 x 28 mm	0.23 kg
		24~48 V	700 mA	33.6 W					
		16~32 V	1050 mA						
		12~24 V	1400 mA						
GPCP-60		40~80 V	700 mA	56 W	short circuit, over current			162 x 42 x 33 mm	0.40 kg
		30~60 V	1050 mA	63 W					
		24~47 V	1250 mA	58.8 W					
		20~42 V	1400 mA						
		18~36 V	1750 mA	63 W					
		16~30 V	2100 mA						

GLG 60-300 W waterproof (IP65, IP67)

● Features:

- CV + CC mode power supply (except GLG-300)
- Universal AC input / Full range
- Built-in active PFC function
- Cooling by free air convection
- 100% full load burn-in test
- IP 67 level (GLG-60, GLG-200, GLG-300)
- IP 65 level (GLG-100, GLG-150)
- Built-in potentiometers to adjust output voltage and current
- Up to 5 years warranty

☐ IP65/67 CE SELV

	Photo	DC voltage	Rated current	Rated power	Protections	Safety & EMC regulations	Working temperature	Dimensions (L x W x H)	Weight					
GLG-60		12 V	5 A	60 W	short circuit, over current, over voltage	EN 55015, EN61347-2-13, EN61000-3-2 Class C	-30°C – +70°C	175 x 56 x 38 mm	0.70 kg					
		24 V	2.5 A											
GLG-100		12 V	8.5	102 W	short circuit, over current, over voltage, over temperature					216 x 66 x 40 mm	0.95 kg			
		24 V	4.2 A	100.8 W										
GLG-150		12 V	12.5 A	150 W						221 x 70 x 45 mm	1.15 kg			
		24 V	6.3 A	151.2 W										
GLG-200		12 V	16.6 A	199.2 W						242 x 96 x 50 mm	1.80 kg			
		24 V	8.33 A	199.92 W										
GLG-300		12 V	25 A	300 W									285 x 96 x 50 mm	2.20 kg
		24 V	12.5 A											

GLSV 35-320 W (IP67)

● Features:

- Constant voltage design
- Built-in active PFC function, PF>0,96 (@230VAC, full load)
- Surge immunity: DM-5KV, CM-10KV
- IP67 design for indoor and outdoor applications
- Isolation class I
- 6 years warranty



	Photo	Output Voltage	Output current	Output power	Protections	Safety & EMC regulations	Working temperature	Dimensions (L x W x H)	Weight
GLSV-035B		12 V	2.92 A	35 W	short circuit, over voltage, overload, over temperature	EN 55015, EN61000-3-2	-40°C – +70°C	199 x 42.5 x 34 mm	510 ± 50g
GLSV-050B		24 V	1.46 A						
GLSV-075B		36 V	0.98 A						
GLSV-100B		48 V	0.73 A	100 W			-40°C – +60°C	164 x 68 x 39 mm	680 ± 50g
GLSV-150B		12 V	8.33 A	150 W				178 x 68 x 39 mm	775 ± 50g
GLSV-200B		24 V	4.17 A					207 x 68 x 39 mm	900 ± 50g
GLSV-320B		36 V	2.78 A					200 W	(12 V & 24 V) 232 x 68 x 43.5 mm (36 V & 48 V) 232 x 68 x 43.5 mm
		48 V	2.08 A	320 W					234 x 98 x 40 mm

GPF 25-60 W waterproof (IP67)

● Features:

- CC mode power supply
- Universal AC input / Full range
- Built-in 3 in 1 dimming function: 0-10V or PWM or resistance
- Cooling by free air convection
- 100% full load burn-in test
- Isolation class II
- Excellent quality / price ratio
- Up to 3 years warranty



	Photo	Voltage range	Rated current	Rated power	Protections	Safety & EMC regulations	Working temperature	Dimensions (L x W x H)	Weight	
GPF-25D		44~72 V	350 mA	25.2 W	short circuit, over current, over voltage, over temperature	EN 55015, EN61347-2-13, EN61000-3-2 Class C	-30°C – +70°C	138 x 43 x 34 mm	0.30 kg	
		22~36 V	700 mA							
		15~24 V	1050 mA							
GPF-40D		72~120 V	350 mA	42 W	short circuit, over current, over voltage		EN 55015, EN61347-2-13, EN61000-3-2 Class C	-30°C – +70°C	153 x 43 x 34 mm	0.40 kg
		36~60 V	700 mA							
		24~40 V	1050 mA							
		18~30 V	1400 mA							
		15~24 V	1750 mA							
GPF-60D		40~80 V	700 mA	56 W	short circuit, over current	EN 55015, EN61347-2-13, EN61000-3-2 Class C		-30°C – +70°C	168 x 44 x 34 mm	0.44 kg
		30~60 V	1050 mA	63 W						
		22~42 V	1400 mA	58.8 W						
		20~36 V	1750 mA	63 W						
		14~28 V	2100 mA	58.8 W						
		12~24 V	2450 mA							

PCC 9-60 W (IP20)

Features:

- Constant current design
- Selectable output current
- Built-in active PFC function
- Universal AC input / Full range (except PCC09W)
- Cooling by free air convection
- Built-in DALI interface (PCC40W-DC-DALI)
- Isolation class II
- AC Phase cut dimming (PCC09W)
- Up to 5 years warranty



Photo	Voltage range	Rated current	Rated power	Protections	Safety & EMC regulations	Working temperature	Dimensions (L x W x H)	Weight	
	13~26 V	350 mA	9 W	short circuit, over voltage	EN 55015, EN61347-2-13, EN61000-3-2 Class C	-20°C – +50°C	109 x 40 x 22 mm	0.065 kg	
	7~13 V	700 mA							
	9~18 V	700 mA	12.6 W						0.068 kg
	26~52 V	350 mA	18 W	short circuit, over voltage, over temperature			-20°C – +50°C	120 x 45 x 28 mm	0.10 kg
	22~45 V	350 mA	40.5 W	short circuit, over current, over voltage		-20°C – +60°C	121 x 81 x 28 mm	0.23 kg	
		500 mA							
		700 mA							
	16~28 V	700 mA							
		900 mA							
		1050 mA							
		1400 mA							
	20~42 V	700 mA	58.8 W	short circuit, over current, over voltage					
		900 mA							
		1050 mA							
		1400 mA							
	60~110 V	350 mA	40 W	short circuit, over voltage		-30°C – +60°C	123 x 81 x 28 mm		
	30~57 V	700 mA							
	20~38 V	1050 mA							
	15~28 V	1400 mA							

PCL 35-80 W (IP20)

● Features:

- Constant current design
- Universal AC input range
- Cooling by free air convection
- Selectable output current
- Isolation class I
- Up to 5 years warranty



	Photo	Voltage range	Rated current	Rated power	Protections	Safety & EMC regulations	Working temperature	Dimensions (L x W x H)	Weight	
PCL35W-MC-MATCH-700		27~54 V	500 mA	13.5~35 W	short circuit, overload, over temperature	EN 55015, EN61347-2-13, EN61000-3-2	-20°C – +50°C	282 x 30 x 21.5 mm	0.25 kg	
	600 mA									
	700 mA									
PCL50W-MC-MATCH-1050			800 mA	23~55 W					0.36 kg	
	925 mA									
	1050 mA									
PCL80W-MC-Match-1550			1200 mA	32~83 W						0.38 kg
	1400 mA									
	1550 mA									

GWP 100 W

● Features:

- Power supply from European voltage 230Vac
- Triple output design 5V, 12V, 24V
- Cooling by free air convection
- Screw terminals
- LED DC OK indicator
- Aluminum housing
- High efficiency
- Up to 5 years warranty



	Photo	Output voltage	Input Voltage	Current rating	Tuning 5V voltage	Output power max	Output power	Efficiency	Working temperature	Dimensions (L x W x H)	Weight
GWP-600		5 V	100-120Vac / max. 2.08 A	10 A	4,75 – 5,5Vdc	104 W	100 W	80 %	0°C – +40°C	98 x 52 x 199 mm	0.04 kg
		12 V		2 A							
		24 V	200-120Vac / max. 1.70 A	1.25 A							



Distributor:

www.glpower.eu

GPF 25-60 W waterproof (IP67)

● Features:

- CC mode power supply
- Universal AC input / Full range
- Built-in 3 in 1 dimming function: 0-10V or PWM or resistance
- Cooling by free air convection
- 100% full load burn-in test
- Isolation class II
- Excellent quality / price ratio
- Up to 3 years warranty

□ IP67 CE LPS

	Photo	Voltage range	Rated current	Rated power	Protections	Safety & EMC regulations	Working temperature	Dimensions (L x W x H)	Weight	
GPF-25D		44~72 V	350 mA	25.2 W	short circuit, over current, over voltage, over temperature	EN 55015, EN61347-2-13, EN61000-3-2 class C	-30°C – +70°C	138 x 43 x 34 mm	0.30 kg	
		22~36 V	700 mA							
		15~24 V	1050 mA							
GPF-40D		72~120 V	350 mA	42 W	short circuit, over current, over voltage		EN 55015, EN61347-2-13, EN61000-3-2 class C	-30°C – +70°C	153 x 43 x 34 mm	0.40 kg
		36~60 V	700 mA							
		24~40 V	1050 mA							
		18~30 V	1400 mA							
		15~24 V	1750 mA							
GPF-60D		40~80 V	700 mA	56 W	short circuit, over current	EN 55015, EN61347-2-13, EN61000-3-2 class C	-30°C – +70°C	168 x 44 x 34 mm	0.44 kg	
		30~60 V	1050 mA	63 W						
		22~42 V	1400 mA	58.8 W						
		20~36 V	1750 mA	63 W						
		14~28 V	2100 mA	58.8 W						
		12~24 V	2450 mA							



GPVP Double isolation cables 25-120 W waterproof (IP67)

● Features:

- Double insulated wires
- Constant voltage design
- Universal AC input / Full range
- Built-in active PFC function, PF > 0.9
- Cooling by free air convection
- 100% full load burn-in test
- Fully encapsulated with IP67 level
- Excellent quality / price ratio
- Up to 3 years warranty

   **IP67 CE SELV**

	DC voltage	Rated current	Rated power	Protections	Safety & EMC regulations	Working temperature	Dimensions (L x W x H)	Weight	
GPVP-25	12 V	2 A	24 W	short circuit, over current, over voltage, over temperature	EN 55015, EN61347-1, EN61347-2-13	-30°C – +70°C	138 x 42.5 x 34 mm	0.360 kg	
	24 V	1 A							
GPVP-40	12 V	3 A	36W	short circuit, over current				149 x 32 x 28 mm	0.23 kg
	24 V	1.5 A							
GPVP-60N	12 V	5 A	60 W	short circuit, over current, over voltage				162 x 42 x 33 mm	0.40 kg
	24 V	2.5 A							
GPVP-90	12 V	7.5 A	90 W	short circuit, overload over current, over voltage, over temperature				190 x 63 x 38 mm	0.391 kg
	24 V	3.75 A							
GPVP-120	12 V	10 A	120 W					250 x 70 x 45 mm	1.05 kg
	24 V	5 A							

GPCP 20-60 W waterproof (IP67)

● Features:

- Constant current design
- Universal AC input / Full range
- Built-in active PFC function
- Cooling by free air convection
- Current versions: 350 mA, 700 mA, 1050 mA, 1250 mA, 1400 mA, 1750 mA, 2100 mA
- 100% full load burn-in test
- Isolation class II
- Excellent quality / price ratio
- Up to 3 years warranty

   **IP67 CE LPS**

	Photo	Voltage range	Rated current	Rated power	Protections	Safety & EMC regulations	Working temperature	Dimensions (L x W x H)	Weight				
GPCP-20		12~48 V	350 mA	16.8 W	short circuit, over current, over voltage, over temperature	EN 55015, EN61347-1, EN61347-2-13	-20°C – +70°C	140 x 32 x 25 mm	0.21 kg				
		9~30 V	700 mA	21 W									
GPCP-35		40~80 V	350 mA	28 W	short circuit, over current		-30°C – +70°C	149 x 32 x 28 mm	0.23 kg				
		24~48 V	700 mA	33.6 W									
		16~32 V	1050 mA										
		12~24 V	1400 mA										
GPCP-60		40~80 V	700 mA	56 W	short circuit, over current				-30°C – +70°C	162 x 42 x 33 mm	0.40 kg		
		30~60 V	1050 mA	63 W									
		24~47 V	1250 mA	58.8 W									
		20~42 V	1400 mA										
		18~36 V	1750 mA	63 W									
		16~30 V	2100 mA										

GLP Professional Line - CC, CV, CC+CP

POWERED BY **MOSO**[®]

		
GEHC	GLDP	GLHP
		
		
Wattage: 26W~150W	Wattage: 42W~320W	Wattage: 60W~200W
Constant current LED power supply - I class, IP67	Constant current with constant power output, programmable LED(time dimming) power supply with dimming function 0-10V (10-100%) / PWM (option) - I class, IP67	Constant current with constant power output, programmable LED(time dimming) power supply with dimming function 0-10V (10-100%) / PWM (option) - I class, IP67, Uin = 249-528VAC
		
GLCP	GLUP	GLTP
		
		
Wattage: 75W~240W	Wattage: 75W~240W	Wattage: 100W~240W
Constant current with constant power output, programmable LED (time dimming) power supply with dimming function 0-10V (0-100%) / PWM (option) or DALI - II class, IP67	Constant current with constant power output, programmable LED(time dimming) power supply with dimming function 0-10V (0-100%) / PWM (option) or DALI - I class, IP67	Constant current with constant power output LED power supply with dimming function 0-10V (1-100%) / PWM (option) or DALI fo high bay lighting - I class, IP67

See the whole catalog



DPV/DMV 20-100 W (IP54)

● Features:

- Constant voltage design
- Universal AC input / Full range
- Voltage versions: 12 V, 24 V
- Cooling by free air convection
- 100% full load burn-in test
- Built-in 2 in 1 dimming function: 0-10 V or resistance (DMV-60D & DMV-80D)
- Isolation class II
- **PWM style dimming output**
- Up to 5 years warranty



	Photo	DC voltage	Rated current	Rated power	Protections	Safety & EMC regulations	Working temperature	Dimensions (L x W x H)	Weight
DPV-20		12 V	12.5 A	20 W	short circuit, over current, over voltage, over temperature	EN 55015, EN61347-2-13, EN61000-3-2 Class C	-40°C – +60°C	134.4 x 34 x 25.4 mm	0.18 kg
		24 V	0.85 A						
DMV-60		12 V	5 A	60 W	short circuit, over current, over voltage		-30°C – +60°C	241.3 x 43.1 x 30 mm	0.63 kg
DMV-60D									0.64 kg
DMV-80D		24 V	3.3 A	80 W	short circuit, over current, over voltage, over temperature		-40°C – +60°C		241.3 x 43.1 x 30 mm
DMV-100			4.1 A	100 W				0.63 kg	
DMVL-100			4.1 A	99.6 W				-25°C – +70°C	

DPCR/DMC 16-40 W (IP54)

● Features:

- Constant current design
- Universal AC input / Full range
- Current versions: 400 mA, 700 mA & 1050 mA
- Cooling by free air convection
- 100% full load burn-in test
- Built-in dimming function: 0-10 V (DMC)
- Isolation class II
- IP 54 (for DPCR-16-400)
- Up to 5 years warranty



	Photo	Voltage range	Rated current	Rated power	Protections	Safety & EMC regulations	Working temperature	Dimensions (L x W x H)	Weight
DPCR-16-400		21~40 V	400 mA	16 W	short circuit, over voltage, over temperature	EN 55015, EN61347-2-13, EN61000-3-2 Class C	-20°C – +50°C	79 x 77 x 26 mm	0.18 kg
DMC-40D		32~55 V	700 mA	38.5 W			-40°C – +55°C	241.3 x 33 x 25.4 mm	0.40 kg
		26~38 V	1050 mA	39.9 W					

Notes